

SAFETY DATA SHEET

C41-0137 NC CLR DIAMOND ULTRA

SECTION 1 – PRODUCT IDENTIFICATION

PRODUCT NAME: C41-0137 NC CLR DIAMOND ULTRA

PRODUCT NUMBER: 01C41-0137

SYNONYMS: PAINT

CAS NUMNER: Mixture

UN NUMBER: UN1263

EMERGENCY RESPONSE GUIDE NUMBER: GUIDE 128

RECOMMENDED USE: Coating

COMPANY INFORMATION: EMCO FINISHING PRODUCTS
470 CRESCENT STREET
JAMESTOWN, NEW YORK 14701
PHONE: (716) 483-1176
FAX: (716) 664-6680

EMERGENCY PHONE: (800) 424-9300 (CHEMTREC)

SECTION 2 – HAZARDS IDENTIFICATION

HAZARD CLASSIFICATION: Flammable Liquid – 1
Skin Corrosive – 2
Eye Corrosive – 2A
Carcinogen – 2
Reproductive Toxin – 1A
Aspiration Hazard – 1

SIGNAL WORD: DANGER



HAZARD PICTOGRAMS:

HAZARD STATEMENTS: EXTREMELY FLAMMABLE LIQUID AND VAPOR
MAY BE FATAL IF SWALLOWED AND ENTERS
AIRWAYS
CAUSES SKIN IRRITATION
SUSPECTED OF CAUSING CANCER
MAY DAMAGE FERTILITY OR THE UNBORN CHILD

PRECAUTIONARY STATEMENTS:



SAFETY DATA SHEET

C41-0137 NC CLR DIAMOND ULTRA

PREVENTION: Read label before use. Keep/store away from heat, hot surfaces, sparks, open flames and other ignition sources. Use only non-sparking tools. Avoid breathing vapors. Do not eat, drink or smoke when using this product. Use only in a well-ventilated area. Wear protective gloves and eye protection. In case of inadequate ventilation, wear respiratory protection.

RESPONSE: If swallowed, do NOT induce vomiting. Get medical attention. If on skin, rinse with plenty of water. If symptoms persist, get medical attention. If inhaled: remove person to fresh air and keep comfortable for breathing. If experiencing respiratory symptoms, get medical attention. If in eyes, rinse thoroughly for 15 minutes. Remove contact lenses and continue washing. Get medical attention. If on clothing, wash before reuse. In case of a fire, fight fire with normal precautions from a reasonable distance.

STORAGE: Store in a closed container. Keep in a cool well-ventilated place.

DISPOSAL: Dispose contents in accordance with federal, state, and local regulations.

SECTION 3 – COMPOSITION / INFORMATION ON INGREDIENTS

SUBSTANCE/MIXTURE:

| INGREDIENT | PERCENT COMPOSITION | CAS NUMBER |
|------------------------|---------------------|------------|
| Toluene | 15-25% | 108-88-3 |
| Ethyl Acetate | 15-25% | 141-78-6 |
| n-butyl acetate | 5-15% | 123-86-4 |
| Methyl Isobutyl Ketone | 5-15% | 108-10-1 |
| Isopropyl Alcohol | 5-15% | 67-63-0 |
| Nitrocellulose | 1-10% | 9004-70-0 |
| Xylene | 1-10% | 1330-20-7 |
| Blown Soya Oil | 1-10% | 68152-81-8 |
| Diocetyl Terephthalate | 1-10% | 6422-86-2 |
| Primary Amyl Acetate | 1-10% | 628-63-7 |

SECTION 4 – FIRST-AID MEASURES

IF INHALED:

Remove to fresh air. If not breathing or breathing is difficult, give oxygen or artificial respiration and get medical attention. Do not perform CPR.

IF SKIN CONTACT:

Immediately wash skin with mild soap and large volumes of water. Remove contaminated clothing. Wash clothing before reuse. Get medical attention if symptoms persist.

IF EYE CONTACT:

Thoroughly flush eyes with large volumes of clean, low pressure water for at least 15 minutes while holding eyelid



SAFETY DATA SHEET

C41-0137 NC CLR DIAMOND ULTRA

open. Remove contact lenses, if worn, after initial flushing and then continue flushing. Get immediate medical attention.

IF SWALLOWED:

Rinse mouth with water. Drink water. Do NOT induce vomiting. If vomiting occurs, keep head lower than hips to prevent aspiration. Get medical attention.

SECTION 5 – FIRE-FIGHTING MEASURES

SUITABLE EXTINGUISHING MEDIA:

Water fog or spray, alcohol resistant foam, dry chemical, carbon dioxide.

UNSUITABLE EXTINGUISHING MEDIA:

Do not use water in a tight stream.

SPECIFIC FIREFIGHTING HAZARDS:

If possible, keep nearby containers cool. Heat may build enough internal pressure to rupture a closed container, potentially spreading the fire and increasing risk. Oxides of carbon and other possible toxic solids, vapors, and/or gases may be emitted.

SPECIAL FIREFIGHTING EQUIPMENT/PROCEDURE:

Wear full protective clothing and self-contained breathing apparatus or air mask. Fight large fires from a safe distance. If possible do not allow discharge runoff into the water environment.

SECTION 6 – ACCIDENTAL RELEASE MEASURES

PERSONAL PRECAUTIONS, PROTECTIVE EQUIPEMENT:

Handle in accordance with good industrial hygiene and safety practice. Use chemical resistant gloves and safety glasses with side shields or goggles. To prevent contact with skin, wear clothing covering all exposed areas.

METHODS AND MATERIALS FOR CONTAINMENT AND CLEAN UP/EMERGENCY PROCEDURE:

Ventilate the area. Avoid breathing dust or vapor. Use a self-containing breathing apparatus or air mask for larger spills. Remove all sources of sparks or ignition. Clean and dispose contaminated area into an appropriate disposal container.

SECTION 7 – HANDLING AND STORAGE

HANDLING:

Handle in accordance with good industrial hygiene and safety practice. Do not smoke near chemicals.

STORAGE:

Keep in cool, well-ventilated area away from any source of heat, sparks, or open flames. Keep container sealed tight when not in use. Ensure proper labeling on the container.



SAFETY DATA SHEET

C41-0137 NC CLR DIAMOND ULTRA

SECTION 8 – EXPOSURE CONTROL / PERSONAL PROTECTION

INGREDIENTS:

| INGREDIENT | OSHA | ACGIH | CERCLA RQ | SARA 302 EHS | SARA 313 | HUMAN CARCINOGEN |
|------------------------|----------------------------|---------------|-------------|--------------|----------|------------------|
| Toluene | No data | No data | None Listed | No | Yes | No |
| Ethyl Acetate | PEL 400 ppm. | TWA 400 ppm. | 5,000 lbs. | No | No | No |
| n-butyl acetate | PEL 200 ppm. | STEL 200 ppm. | 5000 lbs. | No | No | No |
| Methyl Isobutyl Ketone | PEL 100 ppm. | STEL 75 ppm. | 5,000 lbs. | No | Yes | No |
| Isopropyl Alcohol | PEL 400 ppm. | STEL 500 ppm. | None Listed | No | No | No |
| Nitrocellulose | STEL 500 ppm. (vacated) | STEL 500 ppm. | None Listed | No | No | No |
| Xylene | TWA 100 ppm. | STEL 150 ppm. | 1,000 lbs. | No | Yes | No |
| Blown Soya Oil | No data | No data | None Listed | No | No | No |
| Dioctyl Terephthalate | No data | No data | None Listed | No | No | No |
| Primary Amyl Acetate | TWA 100 ppm | TWA 50 ppm. | 5,000 lbs. | No | No | Yes |

RESPIRATORY PROTECTION:

Wear proper safety glasses and gloves. Avoid using contact lenses.

PROTECTIVE CLOTHING:

Wear clothes that protect from exposed skin. Clothing should be removed and washed after chemical usage.

VENTILATION:

Ensure that the area of usage is properly ventilated. If local exhaust ventilation system is not adequate, use a respiratory protection program.

ADDITIONAL MEASURES:

Wash hands before eating, drinking, smoking or using toilet facilities. Proper eyewash and safety shower facilities should be available.

SECTION 9 – PHYSICAL AND CHEMICAL PROPERTIES

PHYSICAL STATE:

Liquid

COLOR:

Varies

ODOR:

Aromatic

ODOR THRESHOLD:

No data available

pH:

MELTING POINT/FREEZING POINT:

No data available

BOILING POINT/RANGE:

>130° F

FLASH POINT:

>0° F

EVAPORATION RATE:

No data available

LOWER EXPLOSIVE LIMIT:

~ 1%



SAFETY DATA SHEET

C41-0137 NC CLR DIAMOND ULTRA

| | |
|---|-------------------|
| UPPER EXPLOSIVE LIMIT: | ~ 13% |
| VAPOR PRESSURE: | No data available |
| VAPOR DENSITY: | No data available |
| SPECIFIC GRAVITY: | 0.923 |
| SOLUBILITY IN WATER: | No |
| SOLUBILITY IN OTHER SOLVENTS: | Yes |
| PARTITION COEFFICIENT (N-OCTANOL/WATER): | No data available |
| AUTO-IGNITION TEMPERATURE: | No data available |
| DECOMPOSITION TEMPERATURE: | No data available |
| VISCOSITY: | No data available |
| VOC: | 5.18 lbs./gallon |

SECTION 10 – STABILITY AND REACTIVITY

| | |
|--|--|
| CHEMICAL STABILITY: | Stable under normal conditions of use |
| HAZARDOUS POLYMERIZATIONS: | None anticipated under normal conditions of use |
| HAZARDOUS DECOMPOSITION PRODUCTS: | None anticipated under normal conditions of use |
| CONDITIONS TO AVOID: | Keep away from heat, sparks, open flame, static electricity, and all ignition sources. |
| INCOMPATIBLE MATERIALS: | Oxidizers |

SECTION 11 – TOXICOLOGICAL INFORMATION

| | |
|--------------------------------------|--|
| MEDICAL CONDITION AGGRAVATED: | Pre-existing medical conditions in the following systems or organs may be aggravated by exposure to this product: Skin (dermatitis), eyes, liver, kidneys, nervous system, respiratory system (asthma, lungs). Repeated or prolonged exposure could produce target organ damage. |
| INHALATION: | High concentrations may lead to Central Nervous System effects, including drowsiness, dizziness, nausea, headaches, paralysis, and possible unconsciousness. High vapor concentrations are irritating to the respiratory system and the eyes. Prolonged or repeated exposure may cause liver or kidney damage. |
| INGESTION: | Product may be harmful or fatal if swallowed, as well as produce potential lung damage. It may produce Central Nervous System effects including dizziness, loss of balance and coordination, coma, or even death. It also is an irritant to the mouth, throat, and stomach. |
| EYES: | The product will potentially cause moderate to significant eye irritation. |



SAFETY DATA SHEET

C41-0137 NC CLR DIAMOND ULTRA

SKIN: Contact with the solution may cause mild to moderate skin irritation. Repeated contact may result in defatting and drying/cracking of the skin, which could result in significant skin irritation and dermatitis (rash). Skin absorption may produce systemic toxicity.

SECTION 12 – ECOLOGICAL INFORMATION

PERSISTENCE AND DEGRADABILITY: No data available
BIO ACCUMULATIVE POTENTIAL: No data available
MOBILITY IN SOIL: No data available
OTHER ADVERSE EFFECTS: No data available

SECTION 13 – DISPOSAL CONSIDERATIONS

WASTE DISPOSAL: Dispose of in accordance with federal, state and local regulations.

SECTION 14 – TRANSPORT INFORMATION

UN NUMBER: UN1263
UN PROPER SHIPPING NAME: PAINT
TRANSPORT HAZARD CLASS: 3
PACKING GROUP: II
CONSTITUENTS: (Toluene & Ethyl Acetate)

SECTION 15 – REGULATORY INFORMATION

TSCA STATUS: All known components of this product are listed or are exempt from listing.

SARA SECTION 311/312:

| | |
|--------------------------|-----|
| ACUTE: | Yes |
| CHRONIC: | Yes |
| FIRE: | Yes |
| REACTIVE: | No |
| PRESSURE RELEASE: | No |

HMIS HEALTH: 2

HMIS FLAMMABILITY: 3

HMIS REACTIVITY: 0



SAFETY DATA SHEET

C41-0137 NC CLR DIAMOND ULTRA

HMIS PERSONAL PROTECTION: X

| |
|---------------------------------------|
| SECTION 16 – OTHER INFORMATION |
|---------------------------------------|

PRODUCT REVISION DATE: 6/5/2018

SDS REVISION DATE: June 5, 2018

SDS REVISION NUMBER: 1